

YY-R4 Series

- With excellent thermal solution
- Easy assembly and maintenance
- High security
- Meet FCC Class 'B' and CE requirement

YY-R420(D:454mm)
YY-R421(D:542mm)

YY-R422(D:454mm)
YY-R423(D:542mm)



The Professional Computer Case Manufacturer

www.yycase.com

YY-R4 Series



Accepts extended motherboard or 8-14 slots passive backplane



Optional 6cm fan for hot air exhaust out



ATX Power supply 300W~600W or Mini redundant 300W~400W



Patented adjustable Card hold-down clamp protecting plug-in cards against vibration



¥ Detachable drive bracket
¥ Multi-angled shock-resistant disk drive bay



Optional 18"/>"120"/"122" Telescopic Sildes w/mounting bracket & screws kits

Vents for drive device with cleanable filter



With Aluminum alloy handles, D shape aluminum handles is by order request

Easy removable 114CFM ball bearing fan (option), with air filter



Front Access USB*2 is available by order request

This is the illustration for model YY-R423, please refer exact spec of each model

SPECIFICATIONS

Model	YY-R420/YY-R422	YY-R421/YY-R423
Case dimension (WxHxD)	19.0" x 7.0" x 17.9" 483mm x 177mm x 454mm	19.0" x 7.0" x 21.3" 483mm x 177mm x 542mm
Motherboard configuration	ATX / 8-14 slots Passive Backplane	Extended ATX / 8-14 slots Passive Backplane
Drive configuration	3 x 5.25" exposed, 2 x 3.5" exposed and 1 x 3.5" hidden	TX / 8-14 slots Passive Backplane
Built in system cooling fan	2 x 9cm Ball Bearing Fan	
Number of slots	7 (maximum to 14)	
Controls	Power switch, Reset switch, Power Alarm buzzer reset, Power on LED, HDD LED, Power error LED	
Air Filter	One removable filter at front panel	
Hold-down Clamp	Including 7 slots of adjustable card retainer	
Power Supply	¥ ATX 12V / EPS 12V ¥ Mini Redundant Hot-Swap UL, CSA, TÜV, CE approved, Doc compliance	
Construction Materials	Recyclable materials Hardened Aluminum alloy handle; Heavy-duty steel Chassis	R422,R423 →CGI* R420,R421 →SPCC+Ni Plated*
EMI	CE/FCC compliant	
Operation temperature	32 to 122 °F (0 to 50 °C)	
Net Weight (w/o power)	13kgs/28.6lbs	14.6kg/32.1lbs
Gross Weight (w/o power)	16kgs/35.2lbs	17.5kg/38.5lbs
Color	Cool gray, black	
Packing	Strengthen carton box with EPE foam	
Options	¥Rear window for 8-14slots passive backplane ¥Telescopic slider 18"/"22" ¥6cm cooling fan, rear mounted ¥9cm cooling fan, front mounted	¥ 6HDD + Fan Cage ¥ 2HDD Cage ¥ Extra Fan Cage ¥ Front USB
Volume of container	3.3cuft/each carton 310pcs/20'container 635pcs/40'container	4.24cuft/each carton 235pcs/20'container 500pcs/40'container

*CG I (Cool Glvanized):R422,R423 *SPCC+Nickel Plated:R420, R421



YEONG YANG TECHNOLOGY Co.,Ltd
12F.,778-1 Chung Cheng Road,
Chung-Ho City,Taipei Hsien, Taiwan, R.O.C
Tel:+886-2-32340020 Fax:+886-2-32340014
E-mail:info@yycase.com.tw
Web Site:http://www.yycase.com

Europe Branch
YEONG YANG TECHNOLOGY GmbH
Mühlenhagen 130,20539 Hamburg,
Germany
Tel:+49-40-780461-0 Fax:+49-40-780461-11
E-mail:info@yeongyang.de
Web Site:http://www.yeongyang.de

U.S.A Contact:
Gigacase Corp.
18459 E. Railroad St., City of Industry
CA91748, USA
Tel:+1-626-854-9289 Fax:+1-626-854-1896
E-mail:info@yeongyang.com
Web Site:http://www.gigacase.com

*All brand names and trademarks are the property of their respective owners.
*Specifications are subject to change without prior notice.